

पनवेल महानगरपालिका ता.पनवेल, जि.रायगड



जा.क्र.पमपा/सा.बां.(श.अ.)/२२२५/प्र.क्र.२४/ ७३८/२०२५

दिनांक २४/०१/२०२५

जाहीर सुचना

पनवेल महानगरपालिका हद्दीतील खारघर येथील प्लॉट-५९A, सेक्टर-१९ येथे खेळाचे मैदान विकसित करणेबाबत. इच्छुकांनी सदरचे निविदा दर दिनांक ३०/०१/२०२५ रोजी सायं ४.०० वाजेपर्यंत महानगरपालिकेच्या बांधकाम(श.अ.) विभागाकडे समक्ष सादर करावीत. सदर दिनांका नंतर प्राप्त झालेले दरपत्रके विचारात घेतले जाणार नाहीत.

SR. NO.	DESCRIPTION OF WORKS	UNIT	QTY	ठेकेदाराने द्यावयाचा दर रक्कम रू.(GST) सहित
1	Providing, supplying and fixing Synthetic Acrylic flooring in 5 layers for skating track on concrete surface for Skating ground	SQM	1, ,	
2	Football ground artificial grass turf 50mm thick on levelled ground surface	SQM	1	
3	Providing, Supplying and fixing basketball turf pp tiles 15.8mm (approved abdfiba testes) on concrete base	SQM	1	
4	Providing, Supplying and fixing tennis turf pp tiles 15.8mm (International Trade Federation approved abdfiba testes) on concrete base	SQM	1	T
5	Providing, supplying and fixing Badminton court turfpp tiles 15.8mm (itf approved abdfiba testes) on concrete base	SQM	1	
6	Providing, Supplying and installation of Tiger Turf Premier, 9 mm pile heighted PE fibrillated yarn that is suitable for both outdoor and indoor cricket practice. Preparing sub Base of gravel oversize metal (200 mm loose), 40mm Trap Metal Over size, 20mm Trap Metal Over size, Gokak Sand, Red Mali Soil by compacting & Watering, etc. Complete.	SQM	1	
7	Lawn Tennis Fix pole Total Height of Pole- 3 Ft 6 Inch Thickness of Pole- 3 MM Dia of Pole- 75 MM Square Total Weight of the Pole- 30 Kg Rachid, With Net Best Quality PU Paint	pair	1	
8	Premium Snooker Table- Size of Table- 12 X 6 Ft Made of Superior Solid Wood 6 Legs Sheesham Frame Made of Imported German Pine Wood Cushion Malaysia Saal, white smooth and Glaze Marble 1.5" thick in 3 Pcs,1 pcs Cue Stand 1 pcs try angle pvc, cloth fine quality 777 gold Ball set Best Quality 1 Lamp Set, 2pcs Stick Ash Wood, 1Powder packet 500 Gm, 12 pcs Tip. 12 pcs Chock, 1pcs Brush,1 Pcs Dust Cover, Adjustable for Levelling Pocket Set made of Brass	piece		
9	Table Tennis Table- Top Thickness- 25 MM Frame Size- 20 X 60 MM Wheel Size- 125 MM Size of Table- 2740 X 1525 X 760 MM Weight of Table- 160 Kg (Approx) Color of Table Top- Blue Complementary 2 Bats & Balls	piece	1	
10	Fixed Football Goal Post Made of 100 MM Iron Round Pipe Pole Size – 24 X 8 Ft Back Support Pipe 50 MM Round With Nylon Net Best Quality Dual Color PU Paint	piece	1	
11	Badminton Pole Fixed Total Height of Pole- 5 Ft 1 Inch Made of 100 MM Round Pipe Rachid with Net Best Quality PU Paint	piece	1	

12	Basket ball - Standard Pole Extension - 2.20 MTR Standard Board Size – 180X105 CMS Board Thickness – 18 MM Acrylic Pole Pipe Size – 150 MM Square Ring Type – Dunking 3 Spring with Nylon Net, Best Quality PU Paint	piece	1	
13	Truss less roof material for badminton hall Span – 17.80 m Arch height – 3.56 m Length – 18.35 m Arch length – 20.65m No of bays – 1 nos Column – 3.5 m hight 1mm thick	SQM	1	
14	Providing, supplying and fixing TURBO VENTILATORS of specifications as , Air ventilator – 22 inch Fan size – 22 inch Fan weight – 5 kg No of blades – 36 Blade thickness = 0.5mm + Top disc – aluminum Bearing – ZZ double bearing, 6002 SKF Fan ring – aluminum Air charge hour – light industrial, Bottom ring - SS	NOS		
			6000000	17
	ELECTRICAL COMPARATIVE	Each	12	M. Carlotte
15	Supply of 16 MTR High GI Polygonal High Stadium Mast as per diamesnion: Top: 150; Bottom: 460; Sections: 2; 670 x 25; PCD: 590; Suitable for upto 12 LED Lights in ASy mmetric Sections: T1-8300; T2-8300 MM; Section Thickness: T1-3; T2-4 MM; OD Base Plate: arrangement and W/s of 50 m/s. Head frame suitable for 3- wire rope suspension Double Drum Single Gear Winch 750 Kg. (Gear Ratio - 50:1),Motor, 6 mm SS Wire Rope (Grade-AISI 316), Compen sating Disc, Manual Operating Handle. (without luminaries, Feeder Pillar, Control Switch & AOL.), Supply with 1.5 HP X 3 Phase Motor .,foundation bolts manufactured from special steel along with nuts, washers, anchor plate and templates, COUNTER weight complete set			
16	Supply of 20 MTR High GI Polygonal High Stadium Mast as per diamesnion: Top: 150; Bottom: 460; Sections: 2; Sections: T1-10860; T2-10000 MM; Section Thickness: T1-3; T2-4 MM; OD Base Plate: 670 x 25; PCD: 590; Suitable for upto 6 LED Lights in ASymmetric arrangement and W/s of 50 m/s. Head frame suitable for 3-wire rope suspension, Double Drum Single Gear Winch 750 Kg. (Gear Ratio - 50:1), Motor, 6 mm SS Wire Rope (Grade-AISI 316), Com pensating Disc, Manual Operating Handle. (without luminaries, Feeder Pillar, Control Switch & AOL.), Supply with 1.5 HP X 3 Phase Motor., foundation bolts manufactured from special steel along with nuts, washers, anchor plate and templates, counter weight complete set	Each	1	
17	LED FLOOD LIGHT LUMINIARE-Panasonic, cradle mounting IP66, IK07, CCT 5700K Flood Light fixture with Die Cast Al housing & Toughned glass, High Operating voltage range of 140V-270V, THD<10%, with Surge protection of 4KV +10KV external ensuring life class of 50000 burning hours @ L70B50, delivering 60000 lumens in 500W with efficacy of >120lm/W, ambient Temp. range -10 Degree to + 45 Degree C, Eq to Panasonic PFLM20ZS8R1	Each	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
18	S&E Junction Box IP66/67 HENSEL or equivalent Grey Polycarbonate Junction Box, IP66, IP67, 93 x 93 x 62mm, KF0200H	Each	1	
19	Supplying & erecting of High definition 2 Megapixel IP IR Dome Camera with following features Image Sensor: minimum 1/2.8" Progressive Scan CMOS, Video Resolution: minimum 1920 x 1080 Video Compression: H.264, H.265 or higher, at least Three individually configurable stream,	Each	1	
20	Supplying, installing, testing & commissioning of 16/20 Ch. Network Video Recorder (NVR), suitable for 2 MP cameras only with HDMI/VGA outputs provided HDMI output of 4K resolution or VGA output with output up to 1920 × 1080. Support H.265 or higher, H.264, MJPEG, Incoming Bandwidth 160Mbps with minimum 2 SATA Hard Disks,	Each		

21	Supplying & erecting 8 TB internal Surveillance HDD suitable for SATA Port of NVR, interface transfer rate 6 GB/S, maximum sustained transfer rate 210 MB/Sec to 213 MB/S. Drive bay supported 08+, Cameras supported up to 64, Cache (MB) 256, Load/Unload Cycle -3000000, Work Load Rating per Year 180TB, MTBF 1000000 Hrs. HTTPS. RoHS, UL, CE certified, duly erected in position in provided NVR as per specification no. CCTV-HDD	Each	1	
22	Supplying & erecting 32" professional LED Monitor with 1920*1080 (Full HD) Display, suitable for 16 channel NVR and following features Brightness: minimum 250 Cd/m2 Contrast Ratio: minimum 1000:1 Viewing angle: 178/178 deg. Response time: maximum 8 ms ,Inputs: HDMI, VGA, BNC, USB, Audio In, Built-in speakers maximum 2 W, Suitable to operate on 100-240 V 50 Hz AC supply and 24/7 Duty Cycle duly erected on wall or table top with standard accessories like wall mount stand and wiring connections etc. complete as per specifications no. CCTV-MON	Each	1	
	Note : All above Items will Execute as directred by Engineer Incharge PMC			

या कामी अटी व शर्ती खालील प्रमाणे-

- १. नमुद केलेले दर हे सर्व प्रकारचे वाहतुक खर्चासह समाविष्ठ असावेत.
- २.सदरची जाहीर सुचना फक्त दर खात्री करणे करीता मागविणेत येत आहे.
- ३.या कामी काही माहीती हवी असलेस बांधकाम(श.अ.) विभागाकडे संपर्क साधावा.
- ४. या कामी दरांची खात्री झालेनंतर जाहीर ई-निविदा मागविणेत येईल.
- ५. प्राप्त जाहीर निविदा सुचना दर स्वीकारण्याचे अथवा नाकारण्याचे अधिकार निविदा समितीला असतील.

(मा.शहर अभियंता यांच्या मान्यतेने)

(राजेश कर्डिले) उप अभियंता पनवेल महानगरपालिका